

TD-4234

BLOOD GLUCOSE MONITORING SYSTEM

7 Sec, 0.7 μ L

Strip-Ejection

Data Transmission Port



FEATURES

- Operating by Graphic User Interface (GUI)
- Display data graphs and charts on screen
- 4 alarm settings
- Rechargeable battery
- Before / After meal (AC/PC) presetable



SPECIFICATIONS

Enzyme Type	GOD
Sample Size	0.7 μ L
Reaction Time	7 seconds
Measurement Range	20 ~ 600mg/dL (1.1 ~ 33.3mmol/L)
Hematocrit Range	30%-55%
Precision	\pm 5% with respect to Standard
Accuracy	\pm 15mg/dL if \leq 100mg/dL; \pm 15% if $>$ 100mg/dL
Ketone Warning	No
Communication	Mini-USB
Power Source	Li polymer
Memory Capacity	400 sets
Day Average	7, 14 days
Daily Alarm	4 daily alarms
Dimension	83.6 (L) x 58.7 (W) x 16.6 (H)mm
Weight	46.4g (with battery)
Operating Condition	10°C(50°F)~40°C(104°F)
Storage Condition	-20°C(-4°F) ~ +60°C(140°F) (Meter); 4°C(39.2°F)~40°C(104°F) (Strip)
Units Per Carton	30
Carton Size	476 (L) x 370 (W) x 400 (H) mm
Cross Weight Per Carton	11.5 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288