

TD-4285

BLOOD GLUCOSE MONITORING SYSTEM

6 Sec, 0.5 μ L

Strip-Ejection



FEATURES

- Before / after meal (AC/PC) presetable
- Ketone warning
- Display calendar and clock when meter standby

SPECIFICATIONS

Enzyme Type	GDH-FAD
Sample Size	0.5 μ L
Reaction Time	6 seconds
Measurement Range	20 ~ 650mg/dL (1.1 ~ 36.1mmol/L)
Hematocrit Range	20%-65%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100mg/dL (5.55 mmol/L); CV < 5% at 100mg/dL (5.55 mmol/L)
Accuracy	± 15 mg/dL if < 100mg/dL : $\pm 15\%$ if ≥ 100 mg/dL
Ketone Warning	Yes
Communication	RS232
Power Source	CR2032 x 1
Memory Capacity	450 sets
Day Average	7, 14, 21, 28, 60, 90 days
Daily Alarm	4 daily alarms
Dimension	96 (L) x 60 (W) x 15 (H) mm
Weight	41.2g (without battery)
Operating Condition	10°C (50°F) ~ 40°C (104°F)
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter) 2°C (35.6°F) ~ 30°C (86.0°F) (Strip)
Units Per Carton	30
Carton Size	476 (L) x 370 (W) x 400 (H) mm
Cross Weight Per Carton	7.5 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugong Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288